NEW HOSPIVAC 400



Available in its three configurations, BASIC, FS and FULL, NEW HOSPIVAC 400 has been designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery. The state-of-the-art 90 l/min oiless and maintenance-free pump provides high performances with excellent suction capacities and max vacuum built up within a few seconds. A clear dashboard along with a full range of accessories and antistatic castors with brakes make it the ideal device for surgical suction and liposuction. The new MPR (Multi Purpose Rail) system enhances the versatility of the Hospivac series for easy and quick exchange of different accessories, with no need for tools. In fact, being equipped with five connections, all CA-MI accessories can be easily accommodated, such as rings of various diameters to fit jars of different sizes and types (2L, 3L, 5L), cannula holders or a medical stainless steel rail where to hook any other type of accessory by means of clamps. The new safety trap bottle is also a new standard accessory in the Hospivac series, bringing up to three the overflow protection systems, besides the valve integrated in the jar and the hydrophobic filter, thus providing the Hospivac series with the highest standards of safety.

| AVAILABLE MODELS AND ACCESSORIES INCLUDED | BASIC | FS | FULL |
|---|-------|----|------|
| Liquid Collection Jar with overflow valve system (different options, see below) | 2 | 2 | 2 |
| Rings to accommodate jars (3 sizes depending on the jar) | 2 | 2 | 2 |
| Safety Trap Bottle (220ml) |] | 1 | 2 |
| Antibacterial & Hydrophobic Filter (single-patient) | 1 | 1 | 2 |
| Silicone Tubes ø 8x14mm (autoclavable) - Patient Tube length 150cm | 1 | 1 | 2 |
| Conical Connector ø 10-11-12mm | 1 | 1 | 2 |
| Air suction inlet | 1 | 1 | 2 |
| Footswitch with intermittent or continuous operation | | 1 | 1 |
| Change-Over System from jar to jar by soft-touch keys | | | 1 |
| Power Cord with Schuko plug | 1 | 1 | 1 |
| | | | |

OPTIONAL ACCESSORIE

- Rings available in three sizes:
- 2000 ml autoclavable jars
- 2000 ml and 3000 ml Flovac® disposable systems - 5000 ml autoclavable jars

Cannula holder to store safely suction tube during operation Footswitch with vacuum regulation function Silicone Fetal Vacuum Cups Standard medical stainless steel rail (25x10 or 30x10) and clamps

TECHNICAL FEATURES

| Motor | — Oiless and maintenance-free piston pump | |
|------------------------------|---|-------------|
| Power Feeding | 220-230V / 50-60Hz | |
| ISO 10079-1 Classification — | —— HIGH VACUUM / HIGH FLOW | |
| Max Vacuum (adjustable) ——— | —— -0.90 bar -90 kPa -675 mmHg | |
| Max free air flow rate | 90 l/min | It ali au |
| Noise Level | 46,4 dBA | Italia |
| Duty cycle | —— Non-stop operation | |
| Weight | — 21 kg (unit alone without accessories) | IVIEQICO |
| Size | cm 46 x 42 x 85 | Touol |
| Years of Warranty | 2 | IOUC |
| Shipping carton | 1 | |
| Place of Manufacturing — | —— Italy | MADE IN ITA |
| CE 0123 | | |

CM005.REV5 EDITION NOVEMBER 2018

CA-MI srl Via Ugo La Malfa 13 - Frazione Pilastro - 43013 Langhirano (PR) - Italy Tel. +39 0521 637133 - 631138 FAX +39 0521 639041 export@ca-mi.it www.ca-mi.it